

Piston Intake Relief Valves

Size

- 4-1/2" minimum waterway

Features

- Standard with a 30° elbow (permitting smoother water flow), adjustable relief valve, retractable knob on hand wheel, and air bleed off
- Permits safe controlled flow to the intake pump and can also be used to draft
- Nine easy turns open and close the valve

Material

- Finish anodized throughout - minimum thickness 0.001"

Specifications

- 280 PSI at 70°F (21°C), without relief valve
- Relief valve - double spring, cartridge type, adjustable from 50 to 200 PSI

Storz x Female Swivel



| Storz | Female Swivel NST (NH) | Length | Width | Height | Aluminum Alloy, 356-T6 Part # |
|-------|------------------------|--------|-------|--------|-------------------------------|
| 4" | 4" | 12" | 8" | 17" | FSGR440F |
| | 4-1/2" | | | | FSGR445F |
| | 5" | | | | FSGR450F |
| | 6" | | | | FSGR460F |
| 5" | 4" | 12" | 8" | 17" | FSGR540F |
| | 5" | | | | FSGR550F |
| | 6" | | | | FSGR560F |

Female Swivel x Male

N



| Male NST (NH) | (2) Female NST (NH) Swivel | Length | Width | Height | Aluminum Alloy, 356-T6 Part # |
|---------------|----------------------------|--------|-------|--------|-------------------------------|
| 4" | 4" | 12" | 8" | 17" | FMGR40F40F |
| | 4-1/2" | | | | FMGR40F45F |
| | 5" | | | | FMGR40F50F |
| | 6" | | | | FMGR40F60F |
| 4-1/2" | 4" | 12" | 8" | 17" | FMGR45F40F |
| | 4-1/2" | | | | FMGR45F45F |
| | 5" | | | | FMGR45F50F |
| | 6" | | | | FMGR45F60F |
| 5" | 4" | 12" | 8" | 17" | FMGR50F40F |
| | 4-1/2" | | | | FMGR50F45F |
| | 5" | | | | FMGR50F50F |
| | 6" | | | | FMGR50F60F |
| 6" | 6" | 12" | 8" | 17" | FMGR60F60F |

Replacement Parts



PV-HDWHL

| Description | Part # |
|--------------------|----------|
| handwheel and knob | PV-HDWHL |
| knob only | PV-KNOB |