

## ADS Outage Gauge

**Applications:**

- set level fill point for manual / visual fill control
- measure outage requirements on mobile tanks

**Feature:**

- open dome bracket

Length	316 stainless steel Standard Outgauge Part #	316 stainless steel Outgauge with J Bar Part #
2'	<b>A800OG2</b>	<b>A800OGJ2</b>
3'	<b>A800OG3</b>	<b>A800OGJ3</b>
4'	<b>A800OG4</b>	<b>A800OGJ4</b>
5'	<b>A800OG5</b>	<b>A800OGJ5</b>

## ADS Gauge Rods

**Application:**

- used to gauge liquid levels in any mobile tank

**Features:**

- ½" x .065 wt hardened 316 stainless steel
- laser engraved scale with ¼" graduations
- rods come in two sections that screw together at the midpoint
- foot marks inscribed on rod at 1' intervals below the inch mark
- heavy duty plastic handle
- available in 4', 8' and 12' lengths

Description	316 Stainless Steel Part #
4'	<b>ADS4GR</b>
8'	<b>ADS8GR</b>
12'	<b>ADS12GR</b>



laser engraving closeup

## ADS Spillguard™ Armored Cables

**Features:**

- 3 or 5 pin connector
- 316 stainless steel armoured cable or yellow rubber cable
- custom lengths available, call 513.874.8499 or 877.582.3569 for more information

**Armored Cables**

Length	3 Pin	5 Pin
15'	<b>A200CA3P15</b>	<b>A200CA5P15</b>
20'	<b>A200CA3P20</b>	<b>A200CA5P20</b>
25'	<b>A200CA3P25</b>	<b>A200CA5P25</b>
50'	<b>A200CA3P50</b>	<b>A200CA5P50</b>

**Rubber Cable <sup>1</sup>**

Length	3 Pin
25'	<b>A200CB3P25</b>

<sup>1</sup> for use with (-M) mini connectors only