



## Reversible Concealed Angle Siamese Body

### Application

- Stainless steel FDC provides water up to 90 stories without auxiliary pumping systems

### Sizes

- Bodies: 4" and 6"
- Snoots: 2-1/2" x 2-1/2" and 2-1/2" x 3"

### Features

- Uniquely designed clappers are fully reversible with perpendicular trunnion, allowing one body to be installed for top or bottom connections
- Concealed unit mounts behind a wall plate; escutcheon sold separately for exposed installation

### Materials

- Body: 316 stainless steel
- Shutters: 4" x 2-1/2": brass  
6" x 3": 316 stainless steel
- Snoots: 316 stainless steel
- Pivot pins: brass on concealed units, stainless steel on exposed units

### Specifications

- 4" x 2-1/2" maximum working pressure: **500 PSI**
- 6" x 3" maximum working pressure: **600 PSI**

### Approvals

- 4" x 2-1/2" is FM Approved
- 6" x 3" is FM and New York Fire Department approved



4" X 2-1/2"  
unpolished



6" X 3"  
unpolished



6" X 3"  
polished

Inlet	(2) Outlets	Description	Stainless Steel Part #
4" NPT	2-1/2" NPT	concealed angle body	4025REV90SS
6" grooved	3" NPT	concealed straight body	DCS6030GSS
6" NPT	3" NPT	concealed or exposed angle body	90CREV6030SS
		concealed or exposed angle body polished	90CREV6030SS-P
reversible fire department connection assembly for concealed or exposed installation with proper identification plate Customer to choose from open snoots below			90CREV6030SSPAT

## Open Snoots



2-1/2" x 3" male  
polished satin



3" x 3" male  
polished satin

Swivel	NPT Thread	PSI	Stainless Steel Female Part #	Stainless Steel Male Part #
2-1/2" NST (NH)	2-1/2"	<b>500</b>	SF250FSS	SM250FSS
	3"	<b>600</b>	SF2530FSS	SM2530FSS
3" NST (NH)	3"	<b>600</b>	SF300FSS	SM300FSS
3" NYFD	3"	<b>600</b>	SF300NYFDSS	SM300NYFDSS

N