

Dixon™ Storz Fittings

FSA-Storz x Rigid Female

Features:

- for use wherever a non-valved, locking coupling is required
- anodized components per MIL-A-8625 Type III Class 1
- Buna-N gaskets
- working pressure: **150 PSI** at 70°F (21°C)
- cast aluminum lock lever assembly on 4", 5" and 6"

Storz x NST Female

Storz Size	NST Female Thread	Forged 6061-T6 Alumium Part #	Price
1½"	1½"	FSA1515F	\$98.80
2"	1½"	FSA2015F	161.70
2"	2½"	FSA2025F	137.95
2½"	2½"	FSA2525F	148.50
3"	2½"	FSA3025F	168.75
4"	2½"	FSA4025F	223.25
4"	3"	FSA4030F	278.10
4"	4"	FSA4040F	316.00
4"	4½"	FSA4045F	336.65
4"	5"	FSA4050F	336.65
4"	6"	FSA4060F	361.85
5"	2½"	FSA5025F	412.40
5"	3"	FSA5030F	412.40
5"	4"	FSA5040F	412.40
5"	4½"	FSA5045F	430.95
5"	5"	FSA5050F	441.00
5"	6"	FSA5060F	452.50
6"	6"	FSA6060F	581.35

**Storz x NPT Female**

Storz Size	NPT Female Thread	Forged 6061-T6 Alumium Part #	Price
1½"	1"	FSA1510T	\$98.80
1½"	1½"	FSA1515T	102.95
1½"	2½"	FSA1525T	209.00
2"	1½"	FSA2015T	161.70
2"	2"	FSA2020T	119.00
2½"	1½"	FSA2515T	137.95
2½"	2"	FSA2520T	156.45
2½"	2½"	FSA2525T	173.70
2½"	3"	FSA2530T	170.65
3"	3"	FSA3030T	269.85
4"	3"	FSA4030T	317.80
4"	4"	FSA4040T	344.95
4"	5"	FSA4050T	336.65
4"	6"	FSA4060T	361.85
5"	3"	FSA5030T	412.40
5"	4"	FSA5040T	412.40
5"	5"	FSA5050T	441.00
5"	6"	FSA5060T	452.50
6"	4"	FSA6040T	554.40
6"	6"	FSA6060T	617.80



P

Storz x NPS Female

Storz Size	NPS Female Thread	Forged 6061-T6 Alumium Part #	Price
1½"	1½"	FSA1515S	\$98.80
2"	1½"	FSA2015S	161.70
2½"	2½"	FSA2525S	148.50
4"	4"	FSA4040S	344.95

